SOAH DOCKET NO. 473-16-4342 PUC DOCKET NO. 45866

§

§

§

§

§ §

§

APPLICATION OF LCRA TRANSMISSION SERVICES CORPORATION TO AMEND ITS CERTIFICATE OF CONVENIENCE AND NECESSITY FOR THE PROPOSED 138-KV TRANSMISSION LINE PROJECT IN WILLIAMSON COUNTY, TEXAS **BEFORE THE STATE OFFICE**

OF

ADMINISTRATIVE HEARINGS

DIRECT TESTIMONY AND EXHIBITS

OF

SERGIO GARZA, P.E. #76629

ON BEHALF OF

APPLICANT LCRA TRANSMISSION SERVICES CORPORATION

July 15, 2016

SOAH DOCKET NO. 473-16-4342 PUC DOCKET NO. 45866 DIRECT TESTIMONY AND EXHIBITS OF SERGIO GARZA

TABLE OF CONTENTS

I.	INTRODUCTION	3
II.	PURPOSE OF TESTIMONY	7
III.	PROJECT OVERVIEW	8
IV.	SUBSTATION SITING AREA FACTORS	22
V.	SUBSTATION CONFIGURATIONS, CONNECTIONS, AND COSTS	25
VI.	ELECTRIC SYSTEM PLANNING PROCESS AND ERCOT RECOMMENDATION	29
VII.	THE PROJECT MEETS THE CRITERIA OF PURA AND OTHER CRITERIA CONSIDERED BY THE COMMISSION	31
VIII.	ELECTRIC SYSTEM ALTERNATIVE IMPROVEMENTS CONSIDERED	33
IX.	SUMMARY AND CONCLUSIONS	34

EXHIBITS INDEX

- Exhibit SG-1 Project Submittal to ERCOT Regional Planning Group
- Exhibit SG-2 Meeting Minutes of Project Approval by ERCOT Technical Advisory Committee
- Exhibit SG-3 Meeting Minutes of Project Approval by ERCOT Board of Directors
- Exhibit SG-4 How Electricity Gets to Your House
- Exhibit SG-5 LCRA TSC's response to comments received though the ERCOT RPG process

SOAH DOCKET NO. 473-16-4342 PUC DOCKET NO. 45866 DIRECT TESTIMONY OF SERGIO GARZA

1		I. <u>INTRODUCTION</u>
2	Q.	PLEASE STATE YOUR NAME AND BUSINESS ADDRESS.
3	A.	My name is Sergio Garza. My business address is: Lower Colorado River Authority, 3505
4		Montopolis Drive, Building D, Austin, Texas 78744.
5	Q.	WHAT IS YOUR OCCUPATION?
6	A.	I am an electrical engineer employed by the Lower Colorado River Authority (LCRA) as
7		Vice President, Transmission Design and Protection.
8	Q.	WHAT IS YOUR EDUCATIONAL AND PROFESSIONAL BACKGROUND?
9	A.	I hold a Bachelor's Degree in Electrical Engineering from the University of Texas at
10		Austin, and I am a licensed Professional Engineer in the State of Texas (License Number
11		76629.)
12		I have over 30 years of experience in the electric utility business, all of which have
13		been in public power. In 1985, I began work at the City of Austin Electric Utility
14		Department (presently Austin Energy) as a Project Engineer in the area of System Control
15		Engineering where I designed relay and control systems for transmission equipment such
16		as transmission lines, large transformers, and substations. In 1990, I transferred to the
17		Generation Department where I engineered electrical projects supporting the reliable
18		operation of power plant facilities and also as a project manager supervising non-electrical
19		projects in City of Austin-owned power plants. In 1994, I was employed by LCRA where
20		I worked in the System Control Section of the Transmission Engineering Department. In
21		1995, I became responsible for the system protection function at LCRA within the
22		Transmission Engineering Department. In 1996, I became responsible for both the system
23		planning and system protection functions as an Engineering Supervisor under the Planning
24		and Project Implementation Department. In 2001, I was promoted to Manager of System
25		Planning and Protection. My department's title was changed in 2014 to Transmission
26		Resource Planning (TRP). In November 2015, I was assigned a different function within
27		LCRA Transmission Services as Vice President Transmission Design and Protection

(TDP). Currently, I am one of four vice presidents in Transmission Services who reports
 directly to the Executive Vice President of Transmission Services at LCRA and Chief
 Operating Officer of LCRA TSC.

I have served as Chair of various Electric Reliability Council of Texas (ERCOT)
working groups supporting Dynamics, System Protection, and Planning. I have
participated in the ERCOT Regional Planning Group (RPG) activities and associated study
and project reviews. I have also served in various North American Electric Reliability
Corporation (NERC) forums, including the Interconnection Dynamics Working Group,
Planning Standards Subcommittee, Disturbance Analysis Working Group, Standards
Evaluation Subcommittee, and AC Substation Equipment Failure Task Force.

- I have also participated in or contributed to other key LCRA and/or local technical
 forums including:
- LCRA Collaborative Operations and Planning forum, which was set up to coordinate the operational and long-term planning needs of LCRA TSC and more than 40 municipally-owned utilities and electric cooperatives whose electric systems connect to LCRA TSC's or for which LCRA TSC provides regulated transmission services.
- Power Improvement Action Committee (PIAC) set up by Austin Energy to investigate electric reliability issues associated with service to sensitive end-users' equipment.
- Presented technical topics at various technical forums including a local chapter of the Institute of Electrical and Electronics Engineers (IEEE); Municipal Electric System Association (MESA); LCRA's Substation, Transmission, Operations, Reliability, Maintenance (STORM) forum; and the Texas Electric Cooperatives (TEC) Engineering Conference.
- Participated in a technical panel supporting a Texas Reliability Entity (TRE)
 workshop on transmission planning-related NERC Reliability Standards.

28 Q. IN YOUR PRESENT CAPACITY, WHAT ARE YOUR RESPONSIBILITIES?

A. The department I oversee provides two primary functions. One of these functions is the
 engineering of designs for LCRA TSC's transmission lines, substations, transformation,
 telecommunication systems, metering facilities, and relay and control systems. This
 function includes the provision of system documentation, coordination with ERCOT for
 system metering requirements, transmission system interconnection agreement
 negotiation, and assistance with asset management, system oversight, system reliability
 analysis, and planning for projects through estimating and alternative analysis.

1 The second function is system protection. This function includes ensuring 2 dependable and secure electric service while protecting the general public, personnel, and 3 electrical equipment from abnormal conditions created when electrical faults occur in the 4 system. Specifically, staff responsible for this function produce protective relay settings, 5 evaluate overall protective relay coordination, conduct fault duty, and conduct equipment 6 rating studies.

7Q.HAVEYOUPREVIOUSLYPERFORMEDWORKRELATEDTO8TRANSMISSION LINE REGULATORY PROCEEDINGS?

9 A. Yes, I have provided supervisory oversight or sponsored testimony in the following Public

Utility Commission of Texas (PUC or Commission) dockets:

Project Name	PUC	SOAH
	Docket	Docket
	No.	Number
Application of the Lower Colorado River Authority for a CCN for a	22762	473-00-2302
138-kV Transmission Line in Culberson, Reeves, Loving, and		
Winkler Counties		
Application of the Lower Colorado River Authority and the LCRA	24380	473-02-0429
Transmission Services Corporation to Amend its CCN for a 138-kV		
Transmission Line in Harris and Waller Counties		
LCRA TSC Rate Case (2002)	25421/	473-02-2037/
	26937	473-03-1051
LCRA TSC Rate Case (2003)	28906	473-04-1662
Application of LCRA Transmission Services Corporation to Amend	28450	473-04-3536
its CCN for a 138-kV Transmission Line in Williamson County		
Application of LCRA Transmission Services Corporation to Amend	29684	473-04-7609
its CCN for a 138-kV Transmission Line in Kendall and Bexar		
Counties		
Application of LCRA Transmission Services Corporation to Amend	29065	473-05-1671
its CCN for a 345-kV Transmission Line in Kendall County		
Application of LCRA Transmission Services Corporation to Amend	29833	473-05-0215
its CCN for a 138-kV Transmission Line in Llano County		
Application of LCRA Transmission Services Corporation to Amend	32934	473-07-0448
its CCN for a 138-kV Transmission Line in Medina and Bandera		
Counties		
Commission's Staff Petition for Designation of Competitive	33672	N/A
Renewable Energy Zones		
LCRA TSC Rate Case (2007)	35020	N/A
Application of LCRA Transmission Services Corporation to Amend	33978	473-07-2585
its CCN for a 345-kV Transmission Line in Caldwell, Guadalupe,		
Hays, Travis, and Williamson Counties		
Application of LCRA Transmission Services Corporation to Amend	37448	473-10-1097
its CCN for the Gillespie to Newton 345-kV CREZ Transmission		
Line in Gillespie, Llano, San Saba, Burnet, and Lampasas Counties		

¹⁰

Application of LCRA Transmission Services Corporation to Amend its CCN for the McCamey D to Kendall to Gillespie 345-kV CREZ Transmission Line in Schleicher, Sutton, Menard, Kimble, Mason, Gillespie, Kerr, and Kendall Counties	38354	473-10-5546
Application of LCRA Transmission Services Corporation to Amend its CCN for a 138-kV Transmission Line in Guadalupe County	39479	473-12-0019
LCRA TSC Rate Case (2011)	39891	N/A
Application of LCRA Transmission Services Corporation to Amend its CCN for the Proposed Blumenthal Substation and 138-kV Transmission Line Project in Blanco, Gillespie and Kendall Counties, Texas	43599	473-15-1589

1 Q. PLEASE DESCRIBE THE PROJECT IN THIS PROCEEDING.

A. The project in this proceeding is the proposed Leander to Round Rock 138-kilovolt (kV)
 Transmission Line Project (Project), which consists of the construction of two new load serving substations in Williamson County and the associated 138-kV transmission line
 required to interconnect the two new proposed substations to the interconnected high
 voltage electrical grid at the existing Leander and Round Rock substations.

Q. WERE YOUR TESTIMONY AND THE PORTIONS OF THE APPLICATION YOU SPONSOR PREPARED BY YOU OR BY KNOWLEDGEABLE PERSONS UPON WHOSE EXPERTISE, JUDGMENT, AND OPINIONS YOU RELY IN PERFORMING YOUR DUTIES?

11 A. Yes, they were.

12Q.IS THE INFORMATION CONTAINED IN YOUR TESTIMONY AND IN THE13PORTIONS OF THE APPLICATION YOU SPONSOR TRUE AND CORRECT TO

- 14 THE BEST OF YOUR KNOWLEDGE AND BELIEF?
- 15 A. Yes, it is.

1		II. <u>PURPOSE OF TESTIMONY</u>
2	Q.	WHAT IS THE PURPOSE OF YOUR TESTIMONY?
3	A.	The purpose of my testimony is to sponsor certain portions of LCRA TSC's application to
4		amend its Certificate of Convenience and Necessity (CCN) filed in this docket on April 28,
5		2016 (Application) and to describe and support:
6 7		1) The need and requirements for the two new load serving substations associated with the Project, including the proposed configuration and costs of the new substations;
8 9 10 11 12		2) The need for the associated 138-kV transmission line that is required to interconnect the two new proposed substations with the existing Leander and Round Rock substations, including the associated substation costs and the reasons why this proposed transmission line is the best solution when compared to other alternatives; and
13 14		3) The electric system analyses used in the planning process, including the analyses performed and reviewed by ERCOT.
15	Q.	WHICH QUESTIONS IN LCRA TSC'S APPLICATION IN THIS DOCKET DO
16		YOU SPONSOR?
17	А.	I sponsor the responses to Questions 7, 11, 14, 15, and 16 in the Application along with
18		associated attachments, Attachments 2, 3, 5, 6, and 7. I co-sponsor Attachment 4 to the
19		Application with Ms. Jessica Melendez as it was amended by the errata filed in this
20		proceeding on June 1, 2016. I also co-sponsor the response to Question 13 of the
21		Application with Ms. Melendez, the responses to Questions 8 and 9 with Mr. Christian
22		Powell, and the responses to Question 4 with Ms. Melendez and Mr. Powell. I also co-
23		sponsor Section 1 of the Leander to Round Rock 138-kV Transmission Line Project
24		Environmental Assessment and Alternative Route Analysis, Williamson County, Texas
25		(EA) prepared by POWER Engineers, Inc. (POWER), which is included as Attachment 1
26		to the Application with Ms. Melendez. Please refer to Exhibit CTP-1 in Mr. Powell's direct
27		testimony for an overview of LCRA TSC sponsorship of the Application in this case.
28	Q.	WHAT HAVE YOU RELIED ON IN SPONSORING THE NEED FOR THE
29		PROJECT?
30	A.	In sponsoring the need for the Project, I have reviewed and relied on the following:
31		• The input about the Project received through the ERCOT RPG stakeholder process;
32		• ERCOT's conclusions in its independent assessment of the Project;

1		• The review and approval of the Project by the ERCOT Technical Advisory
2 3 4 5		 Committee at their May 2014 meeting; The review and approval of the Project by the ERCOT Board of Directors at its June 2014 meeting and subsequently recommending that LCRA TSC proceed with the certification and construction of the Project;
6 7		• The oversight I provided on several electric system planning studies performed by LCRA TSC associated with the Project;
8 9		• My general knowledge of growth-related issues in serving electric load in general, as well as in the Project area specifically;
10 11 12		• Information I reviewed in an engineering study conducted by Pedernales Electric Cooperative, Inc. (PEC) to assess the ability of its distribution system to reliably serve electric load that includes the Round Rock, Cedar Park, and Leander areas;
13 14		• An assessment I directed to validate key findings identified in the PEC engineering study;
15 16		• My discussions with PEC engineering staff and evaluation of information provided by PEC regarding the Project;
17 18		• My electric system planning knowledge of the area's existing transmission system capabilities and opportunities for improvement and optimization; and
19		• The oversight I provided on developing the Project's scope of work and associated
20		cost estimates.
20	Q.	cost estimates.
20 21	Q. A.	cost estimates. III. <u>PROJECT OVERVIEW</u>
20 21 22	-	cost estimates. III. <u>PROJECT OVERVIEW</u> WHY IS THE PROJECT NEEDED?
20212223	-	cost estimates. III. PROJECT OVERVIEW WHY IS THE PROJECT NEEDED? The Project is needed because existing electric system infrastructure is not adequate to
 20 21 22 23 24 	-	cost estimates. III. PROJECT OVERVIEW WHY IS THE PROJECT NEEDED? The Project is needed because existing electric system infrastructure is not adequate to meet the forecasted growth in electric demand in southwestern Williamson County. The
 20 21 22 23 24 25 	-	cost estimates. III. PROJECT OVERVIEW WHY IS THE PROJECT NEEDED? The Project is needed because existing electric system infrastructure is not adequate to meet the forecasted growth in electric demand in southwestern Williamson County. The need for the Project is driven by two key factors for adequately and reliably serving local
 20 21 22 23 24 25 26 27 28 29 	-	In the project estimates. III. PROJECT OVERVIEW WHY IS THE PROJECT NEEDED? The Project is needed because existing electric system infrastructure is not adequate to meet the forecasted growth in electric demand in southwestern Williamson County. The need for the Project is driven by two key factors for adequately and reliably serving local area electric load requirements. These factors are: 1) The existing and forecasted growth in electric demand (i.e., the increase in the number of end-use consumers requiring electric service and the increase in power demands from existing end-use consumers) that has been occurring at a steady pace
 20 21 22 23 24 25 26 27 28 29 30 31 32 	-	 cost estimates. III. <u>PROJECT OVERVIEW</u> WHY IS THE PROJECT NEEDED? The Project is needed because existing electric system infrastructure is not adequate to meet the forecasted growth in electric demand in southwestern Williamson County. The need for the Project is driven by two key factors for adequately and reliably serving local area electric load requirements. These factors are: The existing and forecasted growth in electric demand (i.e., the increase in the number of end-use consumers requiring electric service and the increase in power demands from existing end-use consumers) that has been occurring at a steady pace in the Williamson County area; and The distribution-level service reliability requirements driven by high electric demand that cannot be addressed by adding or upgrading existing distribution

provide a transmission connection to these two new load-serving substations from the
 existing electric grid.

3 Q. DID THE ERCOT RPG REVIEW THE NEED AND SOLUTIONS ASSOCIATED 4 WITH THE PROJECT?

A. Yes. LCRA TSC submitted the Project for ERCOT RPG review in accordance with Section
3.11 of the ERCOT Nodal Protocols. ERCOT posted the project for RPG review as a Tier
1 project on December 10, 2013 (reference Exhibit SG-1).

8 Q. DID ERCOT CONDUCT AN INDEPENDENT ASSESSMENT OF THE NEED FOR 9 AND SOLUTIONS ASSOCIATED WITH THE PROJECT?

A. Yes. In adherence with the established ERCOT project review process, after the RPG
review, ERCOT conducted its own independent assessment of the need for the project as
well as all the technical solutions. ERCOT presented the independent assessment results to
the RPG participants. ERCOT's independent assessment report is provided as Attachment
2 to the Application.

15Q.DID THE ERCOT TECHNICAL ADVISORY COMMITTEE REVIEW THE16PROJECT?

A. Yes, at its May 2014 meeting, the ERCOT Technical Advisory Committee voted, with no
dissent, to approve the Project after ERCOT staff presented the need for the project and the
technical solutions (reference Exhibit SG-2 at page 6 of 7).

20 Q. DID THE ERCOT BOARD OF DIRECTORS REVIEW THE PROJECT?

A. Yes, at its June 2014 meeting, the ERCOT Board of Directors voted unanimously to
approve the Project after ERCOT staff presented the need for the project and the technical
solutions. The ERCOT letter discussing the endorsement of the Project by the Board of
Directors is provided as Attachment 2 to the Application, and the meeting minutes are
provided at page 4 of Exhibit SG-3.

1Q.PLEASE DESCRIBE THE EXISTING ELECTRIC SYSTEM INFRASTRUCTURE2IN THE GENERAL AREA OF THE PROJECT.

3 A. Attachment 7 to the Application shows the general location of existing transmission lines 4 and substations in the Project area. Transmission service in the area consists of two main 5 north-to-south paths: a 138-kV corridor along Interstate Highway 35 (IH 35), and a 138-6 kV corridor along US Highway 183 (US 183). The 138-kV transmission path that runs 7 along US 183 is used to provide connectivity to eight substations (Avery Ranch, Balcones, 8 Kent Street, Buttercup, Whitestone, Blockhouse, Leander, and Seward Junction 9 substations) presently serving most of the area between these two corridors. In total, there 10 are presently 21 substation transformers connected throughout the eight substations in this 11 US 183 corridor. The 138-kV transmission path that runs along IH 35 presently provides 12 connectivity to several substations, including the Round Rock South, Round Rock, and 13 Chief Brady substations. The distance between these two 138-kV transmission paths within 14 this high growth area is as much as nine miles.

15 Q. PLEASE DESCRIBE THE PEC SERVICE AREA IN SOUTHWESTERN 16 WILLIAMSON COUNTY THAT IS THE SUBJECT OF THE APPLICATION.

17 A. PEC provides retail electric service in a broad area of the Texas Hill Country, and has 18 supported the growth of these communities for over 75 years. The PEC retail service area 19 is spread across 24 counties and totals over 250,000 accounts. Williamson County is one 20 of the 24 counties in which PEC provides service. Specifically, retail electric service to the 21 area in southwestern Williamson County, generally between Austin and Leander along US 22 183 and west of IH 35, is primarily served by PEC through the eight electric load-serving 23 substations that I discussed previously. Most of the capacity at these eight substations was 24 installed in the last 20 years to be able to keep pace with the rapidly increasing demand for 25 electricity in the area. The end-use consumers include, but are not limited to, residential, 26 small and large commercial, public offices, emergency response, urgent care facilities, 27 churches, schools, ranch and farm operations, communications towers and systems, and 28 water treatment plants.

1 2

Q. PLEASE DISCUSS THE ELECTRIC SYSTEM'S LIMITATIONS IN SERVING THE AREA ELECTRIC LOAD.

A. There are limitations in serving the area's current and projected electric load with the existing electric infrastructure. These limitations are present in both the distribution and transmission systems that serve the area's electrical power needs. I will first discuss the distribution-related limitations that are driven by both continued area growth and limited electric system infrastructure, followed by a discussion of the transmission-related limitations that are driven mostly by the absence of a transmission source in the high growth area.

10To assist in better understanding several complex technical issues that I discuss in11my testimony, I will start with a brief and basic discussion of how electricity travels from12the power generating station to the end-use consumers.

13 To meet the electric needs of end-use consumers (also called "demand" or "load"), 14 electrical power (or electricity) first travels from power generating plants to the electrical 15 loads through high-voltage transmission lines and voltage transformation equipment 16 connected in a network (grid) configuration at voltage levels (classes) of 345- kV, 138-kV, 17 and 69-kV. For the most part, these are the voltage classes used in the ERCOT high voltage 18 transmission grid. The "mesh-like" interconnected transmission grid configuration helps 19 ensure transmission service reliability such that when one component becomes 20 unavailable, power is safely and automatically re-routed or diverted within the grid to reach 21 its destination. This configuration also assists in grid expansion without having to always 22 connect back to a large source.

23 At the 138-kV and 69-kV voltage level, electrical power is transformed or "stepped 24 down" at a substation through voltage transformers to a distribution-level voltage, which 25 is typically 24.9-kV or 12.5-kV. Depending on the general area and operating practices of 26 the local utilities, substations are located closer or farther apart depending on the density 27 of the electrical loads (i.e., urban or rural). In urban areas, in large part due to population 28 density, it is common for substations to be located two to three miles apart. In some cases, 29 the separation between substations could be even less. This distance allows for safe, 30 reliable, and efficient service as well as effective back-up during emergency restoration, 31 maintenance, or construction efforts.

1 The electricity is then distributed out of the substation at distribution level voltages 2 along distribution lines to the end-use consumers through one last level of voltage 3 transformation typically located near the end-use consumer (pole or pad mounted 4 distribution transformers).

- 5 The level of electricity that flows through the equipment described above must be 6 maintained by the utility provider at a safe level which is within the equipment's rated capacity to avoid electrical overloads and eventual failures. Furthermore, to accommodate 7 8 anticipated electric power needs, contingencies, emergency response, maintenance, and 9 construction efforts, the electrical power flows are typically maintained at or below 10 "planning capacity" levels that are significantly lower than the equipment's rated capacity.
- 11 A simple pictorial representation of how electricity is delivered from the generating 12 substation to the end-use consumer is provided as Exhibit SG-4.

13 STATED PREVIOUSLY THAT LOAD GROWTH HAS POSED **O**. YOU 14 DISTRIBUTION-LEVEL LIMITATIONS IN SERVING END-USE CUSTOMERS 15 IN THE PROJECT AREA. HOW HAS THIS AREA GROWN OVER THE LAST 16 **FEW YEARS?**

- 17 A. This area of Williamson County has experienced significant growth over the last several 18 years. The peak electric demand for PEC electric load in the area has increased by a factor 19 of 1.52 times, from 296.2 MW in 2005 to 452.2 MW in 2015. This corresponds to an 20 electric load annual average growth rate of 4.32 percent per year.
- 21 PEC information indicates that meter growth (i.e., new end-use consumers) 22 between 2001 and 2012 in the southwestern Williamson County area increased at a rate 23 that is approximately 1.5 times the overall PEC system meter growth rate. Over 32,000 24 PEC customer electric meters were added over this 11-year period between 2001 and 2012. 25 The average meter growth for this area has been nearly eight percent per year.

26

Q. **IS THIS GROWTH FORECASTED TO CONTINUE?**

27 A. Yes, the total electric demand served by PEC for the southwestern Williamson County area 28 is forecasted by PEC to reach 486 MW by 2020. This electric load level is 1.22 times the 29 demand for electricity in 2014 in this area. The electric load growth forecast provided 1 2 annually by PEC aligns with recent growth history for the area and, at 4.34 percent per year, is similar to the 2005 to 2015 electric load annual average growth rate.

3 Q. HOW HAS THE AREA GROWTH AFFECTED ELECTRIC SERVICE 4 REQUIREMENTS?

5 A. As the area continues to transition from mostly rural to mostly urban in the form of new 6 residential subdivisions, small and large commercial development, emergency response 7 facilities, churches, schools, and other civic service facilities, new load-serving substation 8 capacity and distribution infrastructure is required to continue to provide adequate and 9 reliable electrical service. As I stated previously, most of the capacity at the existing eight substations was installed in the last 20 years to be able to keep pace with the rapidly 10 11 increasing demand for electricity in the area. The addition of new capacity has been 12 achieved mostly by connecting new substations to available 138-kV transmission lines in 13 the area between Austin and Leander or by increasing the transformer capacity at existing 14 substations.

15 In spite of the high and fast growth over the last 20 years, PEC has been able to 16 manage this growth without adding new transmission lines to this specific area in over 15 17 years. The last transmission line built in the area was the four-mile Jollyville to Buttercup 18 Ranch 138-kV transmission line constructed in 2000. However, as the growth in electric 19 demand continues and as it develops further east away from the US 183 path, PEC has 20 exhausted opportunities to effectively, efficiently, and reliably serve the continued demand 21 for electricity from load-serving substations whose capacity may be increased or from new 22 substations that may be sited adjacent to existing transmission lines. Left unaddressed, the 23 continued growth will result in equipment overloads and excessive voltage drop negatively 24 impacting electric service to a broad area in Williamson County.

Q. WHY IS EXCEEDING THE EQUIPMENT CAPACITY RATINGS AND EXCESSIVE VOLTAGE DROP A CONCERN THAT MUST BE ADDRESSED BY UTILITIES?

A. Electrical loading exceeding equipment capacity ratings is a significant concern because
 allowing equipment to carry more electrical power than the equipment capacity rating may
 result in damage to the equipment (e.g., transformers, electrical switches, etc.) and a

subsequent loss of electric service. On distribution lines, allowing the lines to carry more
 electrical power than the line rating, in addition to damage and subsequent loss of service,
 may also result in the line sagging beyond its limits and into underlying objects resulting
 in a public safety concern.

5 Similarly, excessive voltage drop is of concern because this abnormal operating 6 condition can result in damage to, or poor performance of, end-use consumer electrical 7 equipment. Furthermore, the substation's and transmission grid's ability to support normal 8 voltage deviations is significantly reduced.

9 Q. WHAT DO YOU MEAN BY SAYING THAT EXCESSIVE VOLTAGE DROP CAN

10

RESULT IN POOR PERFORMANCE OF END-USE CONSUMER EQUIPMENT?

A. When the operating voltage is not within an appropriate range, electrical equipment such
 as air conditioners, lighting and electronic equipment (e.g., televisions, computers, cash
 registers) may not function properly or at all.

14 Q. WILL THE GROWTH FORECASTED FOR THE AREA AFFECT SERVICE 15 RELIABILITY?

16 A. Yes it will, absent the Project.

17 Q. PLEASE DESCRIBE THESE SERVICE RELIABILITY CONCERNS AND THE 18 STEPS TAKEN TO ADDRESS THEM.

- A. Due to growing concerns about how to support the area's recent and forecasted growth,
 PEC commissioned an engineering study to identify the effectiveness of its electric
 distribution system in meeting the growth in electric demand and to identify system
 improvements that ensure PEC distributes power in a safe, reliable, and cost-effective
 manner. The study revealed that continuing to serve the electrical needs of the area from
 the existing load-serving substations will result in the following:
- 25

26

27

28

- Loss of electric service to a large number of end-use consumers in this area;
- Loading levels exceeding equipment capacity, leading to widespread outages;
- Voltage levels falling below acceptable operational limits, leading to widespread outages; and
 - Decreased electric system efficiencies due to increased electric system losses.

Specifically, the study revealed that as a result of the high electric load growth projected for the area, 42 percent of the transformers will exceed their rated capacity and 90 percent will exceed their planning capacity by 2020. Furthermore, on the distribution side, electrical loading on 27 distribution lines out of the eight substations is projected to exceed rated capacity by 2020, and 10 distribution lines out of four of the substations are projected to reach excessive voltage drop in the same time period.

In summary, the area's high electric load growth, coupled with the limited available
electric delivery system, collectively confirm that the present electric system's capability
to reliably and adequately serve the electric load is near its limits and will soon be
exceeded. The PEC-commissioned engineering study is provided as Attachment 6 to the
Application.

12 Q. WHAT ACTIONS DID PEC TAKE IN RESPONSE TO THE FINDINGS IN THE 13 ENGINEERING STUDY?

A. In June 2012, PEC communicated to LCRA TSC that the need for several new load-serving
substations should be addressed in the upcoming annual planning cycle. In a letter dated
July 12, 2013, PEC reiterated the need for the two load-serving substations (see Attachment
6 to the Application).

18 Q. DID LCRA TSC VALIDATE THE FINDINGS IN THE PEC-COMMISSIONED 19 ENGINEERING STUDY?

20 A. Yes, LCRA TSC verified the key findings in the engineering study.

Q. WHAT FACTORS DID LCRA TSC CONSIDER IN VALIDATING PEC'S CONCLUSION THAT TWO NEW SUBSTATIONS ARE REQUIRED IN THE PROJECT AREA?

A. LCRA TSC considered several factors in validating PEC's conclusions regarding the need

- 25 for the two new substations. Among the most important are the following:
 - PEC's conclusions are based on engineering assessment findings and recommendations that LCRA TSC verified by conducting power flow assessments associated with area infrastructure and electric load projections;
 - PEC's conclusions are based on known and measurable electric load growth; and

26

27 28

• PEC's conclusions are based on engineering and utility practices that would be employed by any other electric service provider in the business to provide reliable, cost-effective, and efficient electric service.

4 Q. PLEASE DISCUSS THE POWER FLOW ASSESSMENT LCRA TSC 5 CONDUCTED TO VALIDATE KEY FINDINGS IN PEC'S ENGINEERING 6 STUDY.

A. The assessment LCRA TSC conducted to validate the key findings identified in PEC's engineering study consisted of three components. The first component was to validate the forecasted electric load growth stated in the PEC study. The second component was to assess the performance of the area's existing electric distribution system at the forecasted electric load levels. The third component was to reassess the same system at the same loading levels with the two new substations in service. LCRA TSC utilized industry-standard power flow analysis software to conduct the assessment

14 Q. WHAT WERE THE CONCLUSIONS OF LCRA TSC'S ASSESSMENT OF PEC'S 15 SYSTEM IN SOUTHWESTERN WILLIAMSON COUNTY?

16 A. Based on its assessment, LCRA TSC concluded the following:

- 17 1. The electric load forecast in the PEC study, a key driver of the need and timing for 18 the Project, is reasonable. LCRA TSC's review of the electric load forecast data 19 shows that the forecasted load levels in the PEC study align closely with historical 20 electric load growth for the PEC system, for the broader Central Texas area, and 21 for the southwestern part of Williamson County. This finding is also consistent 22 with the City of Cedar Park's statement during the ERCOT RPG project review 23 process that "Williamson County continues its nation-leading growth."
- 24
 2. PEC's electric distribution system in southwestern Williamson County cannot
 25
 26
 26
 27
 28
 29
 29
 20
 20
 20
 20
 21
 22
 23
 24
 25
 26
 27
 28
 29
 29
 20
 20
 20
 20
 20
 20
 20
 20
 21
 22
 23
 24
 25
 26
 27
 28
 29
 29
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20
 20</l
 - a) The electric loading of all Avery Ranch Substation transformers will exceed the transformer nameplate rating, with one of the transformers exceeding its rating by as much 32.2 percent.
 - b) The electric loading of distribution lines out of the Avery Ranch Substation will exceed the conductor planning capacity, with one of the lines exceeding this capacity by as much as 52 percent.

27

28 29

30

31

32

1

2

c) The electric losses out of the Avery Ranch Substation will exceed normal
levels, in some cases reaching as high as 11 percent.
d) The voltage out of the Avery Ranch Substation will fall below acceptable levels, in most cases falling as low as 94.1 percent.
e) The electric loading of distribution lines out of the Leander Substation will start to exceed acceptable levels.
f) The electric losses out of the Leander Substation will reach 5 percent, exceeding normal levels.
g) The electric loading of one of the Seward Junction Substation transformers will exceed transformer nameplate ratings, with one of the transformers exceeding its rating by as much 17.9 percent.
h) The electric losses out of the Seward Junction Substation will reach 5.9 percent, exceeding normal levels.
i) The voltage out of the Seward Junction Substation will fall below acceptable levels to 98.3 percent.
3. The addition of the two new substations that are associated with the Project will
effectively and efficiently support the forecasted electric load levels. The LCRA
TSC-conducted assessment revealed that the proposed electric system additions
will support and accommodate existing and forecasted electric load as follows:
a) The electric loading of the Avery Ranch Substation transformers will be maintained within acceptable levels and reduced to below 90 percent.
b) The electric loading of distribution lines out of the Avery Ranch Substation will be maintained within acceptable levels and reduced to less than 60 percent.
c) The electric losses out of the Avery Ranch Substation will be maintained within 4 percent.
d) The voltage out of the Avery Ranch Substation will be maintained within acceptable limits at or above 120 Volts.
e) The electric loading of distribution lines out of the Leander Substation will be maintained within acceptable levels and reduced to less than 60 percent.
 f) The electric losses out of the Leander Substation will be maintained within 4 percent.
g) The electric loading of the Seward Junction Substation transformer will be maintained within acceptable levels and reduced to below than 90 percent.
h) The electric losses out of the Seward Junction Substation will be maintained within 4 percent.
i) The voltage out of the Seward Junction Substation will be maintained within acceptable limits at or above 120 Volts.

1 One of the present limitations addressed by the Project is that the existing substations have 2 become too remote from significant new load growth areas to provide effective, efficient, 3 flexible, and cost-effective electric service. This distance constraint will only continue to 4 worsen as development occurs, particularly near and generally east of the Ronald Reagan 5 Boulevard and FM 1431 intersection for Substation 1 and the Ronald Reagan Boulevard 6 and Crystal Falls Parkway intersection for Substation 2 (i.e., even further away from the 7 existing substations in the area).

8

Q. DID LCRA TSC COMMUNICATE THESE FINDINGS TO PEC?

9 A. Yes, at a June 23, 2015 meeting, I communicated the findings of the LCRA TSC assessment to PEC staff. The objective of this meeting was to ensure that the basic engineering assumptions (regarding, e.g., electric load forecast and PEC delivery system infrastructure) used in LCRA TSC's assessment had not changed significantly and to ensure any PEC-known deficiencies in the general area were not overlooked. PEC validated these assumptions and agreed with LCRA TSC's technical assessment findings.

At that meeting, PEC also reiterated the high electric load growth that is forecasted for the study area. Additionally, PEC noted that, consistent with PEC planning criteria, a more urban-type area requires additional substation transformer capacity to provide backup electric service during emergency conditions. Similarly, PEC plans for feeders to operate below their rated capacity for the same reason.

20 Q. HOW WILL THE TWO NEW SUBSTATIONS LCRA TSC AND PEC IDENTIFIED 21 BE CONNECTED TO THE EXISTING GRID?

A. The new substations will be connected to the existing grid via a new 138-kV line fromLeander to Round Rock.

Q. WHAT FACTORS WERE CONSIDERED IN IDENTIFYING THE POTENTIAL END POINTS FOR THIS NEW 138-KV TRANSMISSION LINE?

- A. The potential end points were initially identified by LCRA TSC based on the followingfactors:
- The proximity to the Project area where the two new substations are needed to be constructed;

1 2		• The need to provide transmission service to each of the two new substations in a loop-connected configuration from different points of the electric grid;
3 4		• The requirement to avoid results that cause the electric grid to violate ERCOT and NERC performance requirements;
5 6		• The need to optimize the use of existing facilities that are connected to the ERCOT grid, thereby reducing the requirement to construct additional new substations;
7 8		• The need to provide electrical connectivity that will support the power flows anticipated on the transmission line associated with the Project; and
9 10		• The expansion capability of the substation property to accommodate the new 138- kV transmission line terminations associated with the Project.
11		Based on these factors, nine potential end points-using both existing and new
12		substations—were identified for further study.
13	Q.	WHAT ATTRIBUTES MAKE THE TWO SELECTED END POINTS MORE
14		EFFECTIVE WHEN COMPARED TO THE OTHER POTENTIAL END POINTS?
15	A.	Primarily, the combination of the Leander and Round Rock end points most cost-
16		effectively addresses the reliability needs of the Project when compared to the other end
17		point combinations considered. Furthermore:
18 19		• The combination of the Leander and Round Rock substations as the Project end points did not violate ERCOT and NERC electric grid performance requirements;
20 21		• The Round Rock Substation provides the strongest transmission source for the new transmission line;
22 23 24 25 26 27		• Electric service reliability is improved to a larger number of end-use consumers (e.g., the Round Rock Substation presently serves a total electric load of approximately 100 MW and thus the benefit of an additional transmission connection is significantly greater when compared to a connection to another substation, such as Chief Brady, where the electric load is significantly less, at approximately 20 MW); and
28 29		• All end-use consumers served out of the Leander and Round Rock substations will benefit from an additional transmission source into those substations.
30	Q.	HOW DO THE LEANDER AND ROUND ROCK SUBSTATIONS BENEFIT
31		FROM THE ADDITION OF AN ADDITIONAL TRANSMISSION LINE
32		INTERCONNECTION FROM THE PROJECT?
33	A.	The Project provides an additional transmission source at the Leander Substation that,
34		based on year 2020 electric load levels and at normal system conditions, provides

approximately 91 percent of the power into the Leander Substation. Thus, the Project is a
 very strong 138-kV transmission source to the Leander Substation. Similarly, under certain
 contingency conditions that naturally divert the electric power flow into the Round Rock
 Substation, the Project will also provide a strong 138-kV transmission source into the
 Round Rock Substation by providing the majority of electric power from the west.

In other words, the Project contributes significantly to the electric power requirements at each of the end points in a manner that positively supports electric service reliability to end-use consumers served from these two substations.

9 Q. CAN THE TWO NEW SUBSTATIONS BE CONNECTED TO THE EXISTING 10 GRID AT ONE END POINT ONLY (E.G., ONLY AT LEANDER SUBSTATION)?

A. No. Given the size of the electric load that will be served from the two new substations,
the new 138-kV transmission line connecting those substations to the grid cannot be
reliably connected to one end point only. A line connected at one end only is referred to as
a "radial-connected" configuration. The transmission line associated with the Project must
be connected at the two end points to establish a "looped-connected" configuration.

16 Q. CAN THE PROJECT BE LOOPED-CONNECTED FROM THE WESTERN SIDE 17 OF THE PROJECT AREA ONLY?

A. No. Several transmission alternatives where both end points are on the western side of the
 Project area were studied by LCRA TSC and ERCOT. Overall, none of those alternatives
 performed as effectively as the Project.

Q. DID ERCOT AGREE WITH THE END POINTS IDENTIFIED BY LCRA TSC FOR EVALUATION?

A. Yes. When LCRA TSC filed the Project with ERCOT for ERCOT RPG review and
 ERCOT independent assessment, all nine end points identified by LCRA TSC were also
 considered by ERCOT. In its independent assessment, ERCOT evaluated another existing
 substation in the Project area as a tenth potential end point for the Project (Westinghouse
 Substation). Ultimately, the ERCOT RPG, ERCOT independent assessment, ERCOT
 TAC, and ERCOT Board of Directors all recommended the Project utilizing the Leander
 and Round Rock Substation end points.

6

7

1Q.PLEASE DESCRIBE THE TRANSMISSION SYSTEM LIMITATIONS IN2SERVING THE AREA ELECTRIC LOAD.

3 A. As I previously discussed over the last several pages of testimony, there is a paramount 4 need for adding two load-serving substations to reliably, efficiently, and cost-effectively 5 provide electric power to the area. In order to provide the necessary transmission level 6 service to those two electric load-serving substations in the area of electric load growth, a 7 new transmission line must be constructed that connects at different points of the existing 8 interconnected electric grid. Thus, the most obvious transmission-related limitation is that 9 this broad, high growth area does not have any transmission source of electrical power 10 from which to connect the electric load-serving substations to the interconnected ERCOT 11 electric grid. Existing transmission lines in the area consist of two main north-to-south 12 paths: 138-kV corridors along IH 35 and US Highway 183. The distance between these 13 two transmission paths is as much as nine miles. This configuration leaves a wide gap in 14 which electric load between the existing lines has to be served remotely and thus 15 ineffectively, with significantly less reliability, higher losses, little to no flexibility to 16 address emergency conditions, and eventually more frequent and extended power 17 interruptions.

18 Q. DOES THE PROJECT ADDRESS ALL THE IDENTIFIED ELECTRIC SYSTEM 19 REQUIREMENTS?

A. Yes, the Project provides an appropriate transmission source to connect the two new
 substations from the existing electric transmission grid thus supporting the area's projected
 future development in terms of electric demand.

Q. DOES THE PROJECT REQUIRE ADDITIONAL TRANSMISSION PROJECTS TO BE CONSTRUCTED TO MEET ITS INTENDED OBJECTIVE?

A. No, it does not. As demonstrated in the LCRA TSC transmission assessment and the
ERCOT independent assessment, the Project effectively addresses the stated need without
requiring other transmission level infrastructure to be constructed. Stated another way,
LCRA TSC's studies and ERCOT's independent assessment confirmed that the ERCOT
grid is sufficiently robust at the Leander and Round Rock substations that additional
projects are not required to interconnect this Project at those locations with the associated

loads that will be served out of the two new proposed substations. This is a planning
 consideration and a key area of focus during the ERCOT independent assessment phases.
 As stated above, the Project provides an appropriate transmission source to connect the two
 new substations from the existing electric transmission grid, thus supporting the area's
 projected future development in terms of electric demand.

6 Q. DO ALL OF THE ROUTING OPTIONS PROPOSED IN THE APPLICATION 7 ADDRESS THE NEED FOR THE PROJECT?

A. Yes, any of the 31 routes filed in the Application address the need for the Project by
providing a diverse set of options for a transmission source for each of the two new
substations that are components of the Project. Likewise, any combination of route
segments presented in the Application that terminate at the Project end points and that
provide connectivity options for both of the new substation siting areas would also address
the need for the Project.

14 Q. DOES THE PROJECT COMPLY WITH PUC, ERCOT, AND NERC 15 REQUIREMENTS?

- 16 A. Yes, the Project complies with PUC, ERCOT, and NERC requirements.
- 17

IV. <u>SUBSTATION SITING AREA FACTORS</u>

18 Q. PLEASE DESCRIBE THE PHYSICAL COMPONENTS OF THE PROJECT 19 RELATING TO SUBSTATION SITING AREA FOR SUBSTATION 1.

A. The two new substations associated with the Project are needed to serve the existing and continued growth in electric load requirements in the area. The substations must serve the area electric load reliably (i.e., within short distances to the electrical load and within supportable facility loading levels), effectively (i.e., within acceptable voltage drop), and efficiently (i.e., without excessive electric losses). They must also be sited in a generally flat area outside of the floodplain with sufficient space to accommodate necessary equipment.

For Substation 1, LCRA TSC proposes to build the substation on approximately 5 to 7 acres of land located within a substation siting area northeast of the intersection of Ronald Reagan Boulevard and FM 1431. This substation siting area, approximately 2.4

1		square mi	iles, as delineated by PEC, effectively aligns with the overall objective of the
2		Project be	ecause it:
3 4 5 6		f I	Balances the requirements identified in the PEC engineering study and the input from various area public officials received during the ERCOT project review phase in December 2013 as well as in the City of Cedar Park's response dated March 13, 2015 to LCRA TSC's Consultation Letter.
7 8 9 10		i	Balances the consideration for continued high density development in the area immediately to the west with less dense area options to the east and does so without compromising the ability to provide or receive effective and efficient back-up service to or from area substations.
11 12			Is located within the PEC certificated service boundary, and therefore it will effectively optimize the use of the substation to a broad area.
13 14 15 16 17		(f I	Is within a reasonable proximity to existing load-serving substations in the area (Avery Ranch, Kent Street, Whitestone, and Blockhouse substations), allowing for effective and efficient operation of the electric system, as I verified through power flow assessments and by a review of the PEC distribution system infrastructure in the area.
18 19			Is sufficiently sized to accommodate several alternatives for installing a 5-7 acre substation within the technically required location for an effective solution.
20		6. I	Is within close proximity to the existing and future electric load to be served.
21		7. 1	Maximizes the substation's ability to efficiently serve future development.
22 23			Best uses available distribution infrastructure, minimizing the need for additional infrastructure.
24 25			Provides the immediate ability for Substation 1 to back up existing area substations during emergencies,
26 27			Allows for appropriate alignment associated with substation location practices in urban areas that are approximately 2-3 miles apart.
28	Q.	DO ALL	OF THE POSSIBLE SUBSTATION SITES IDENTIFIED IN SITING
29		AREA 1	MEET THE OBJECTIVE OF THE PROJECT?
30	А.	Yes, all ei	ight substation sites identified within substation siting area 1 meet the objective
31		of the Pro	ject.
32	Q.	DOES A	NY ONE SITE STAND OUT AS THE BEST SITE FOR LOCATING
33		SUBSTA	TION 1?
34	A.	No. All of	f the possible identified sites are located within the siting circle and thus all meet
35		the object	ive of the Project.

1Q.PLEASE DESCRIBE THE PHYSICAL COMPONENTS OF THE PROJECT2RELATING TO SUBSTATION SITING AREA 2.

A. For Substation 2, LCRA TSC proposes to build the substation on approximately 5 to 7
 acres of land located within a substation siting area near the intersection of Crystal Falls
 Parkway and Ronald Reagan Boulevard. This substation siting area, approximately 2.4
 square miles, as delineated by PEC, effectively aligns with the overall objective of the
 Project because it:

- Balances the requirements identified in the PEC engineering study and the input
 from various area public officials received during the ERCOT project review
 phase in December 2013.
- 112.Balances the consideration for continued high density development in the area12immediately to the west with less dense area options to the east and does so13without compromising the ability to provide or receive effective and efficient14back-up service to or from area substations.
- 15 3. Is located within the PEC certificated service boundary.
 - 4. Is within a reasonable proximity to existing load-serving substations in the area (Blockhouse, Leander, and Seward Junction substations).
 - 5. Is sufficiently sized to accommodate several alternatives for installing a 5-7 acre substation within the technically required location for an effective solution.
- 20 6. Is within the existing and future electric load to be served.
- 21 7. Maximizes the substation's ability to efficiently serve future development.
- 8. Optimizes the use of available distribution infrastructure minimizing the need for additional infrastructure.
- 249.Provides the ability for Substation 2 to back-up existing area substations during25emergencies.
- 2610.Allows for appropriate alignment associated with substation location practices in
urban areas that are approximately 2-3 miles apart.

Q. DO ALL OF THE POSSIBLE SUBSTATION SITES IDENTIFIED IN SITING AREA 2 MEET THE OBJECTIVE OF THE PROJECT?

30 A. Yes, all eight substation sites identified within substation siting area 2 meet the objective
31 of the Project.

16

17

18

Q. DOES ANY ONE SITE STAND OUT AS THE BEST SITE FOR LOCATING SUBSTATION 2?

A. No. All of the possible identified sites are located within the siting circle and thus all meet
the objective of the Project.

5 Q. WHAT ARE THE IMPACTS OF CONSTRUCTING THE NEW SUBSTATION(S)
6 OUTSIDE OF THE IDENTIFIED SUBSTATION SITING AREAS?

- 7 Broadening the siting areas would significantly decrease the value and effectiveness of the A. 8 service they are intended to provide. Siting either Substation 1 or Substation 2 outside its 9 respective substation siting area delineated by PEC reduces the effectiveness and efficiency 10 of the Project by decreasing the ability of the Project to safely, reliably, and efficiently 11 serve the area's long-term future development needs. If the substations are not located 12 within the identified areas, the load-serving requirements out of the substations may not 13 develop as planned and additional substations sites may be required sooner than would 14 otherwise be necessary. Furthermore, siting Substation 1 or Substation 2 outside its 15 respective substation siting area does not assist in minimizing the need for additional 16 infrastructure both in the immediate term as well as long-term. Siting Substation 1 or 17 Substation 2 outside its respective substation siting area introduces risk and will require 18 that additional infrastructure be installed to compensate for the less effective site selection. 19 Several critical factors, of the ten noted previously, would be compromised. Siting 20 Substation 1 or Substation 2 outside its respective substation siting area would not only 21 result in a higher initial cost, but it would also result in a continued higher cost for operation 22 and maintenance that will have to be managed for the life of the assets. These unnecessary 23 costs are paid for by PEC members.
- 24 25

V. <u>SUBSTATION CONFIGURATIONS, CONNECTIONS, AND</u> <u>COSTS</u>

26Q.PLEASE DESCRIBE THE WORK ASSOCIATED WITH THE NEW27SUBSTATIONS AND THE CONNECTIONS AT THE END POINTS.

A. Regarding the substation work associated with this Project, LCRA TSC will construct the
 two new substations (Substation 1 and Substation 2), add 138-kV line termination facilities
 at the existing Leander substation, and coordinate with Oncor at the existing Round Rock

Substation. The substation configuration and connection facilities at each of these sites are
 described in more detail below.

3 End Point at Leander Substation

4

5

6

7

8

9

25

26

The connection of the Project to the existing Leander Substation requires certain modifications at that substation. The LCRA TSC portion of work at the Leander Substation consists of adding:

- One 138-kV A-frame bay
 - One 138-kV circuit breaker
 - Three 138-kV disconnect switches
- Associated protective relaying and control equipment (inside PEC's existing control house)
- 12 Additional work inside the Leander Substation to be provided by PEC consists of extending
- 13 the 138-kV buss work owned by PEC.
- 14 End Point at Round Rock Substation

The connection of the Project to the existing Round Rock Substation requires certain modifications at that substation. The LCRA TSC work inside the Round Rock Substation is limited to the addition of telecommunications equipment that support the control systems associated with the Project. All major work inside the Round Rock Substation to connect the Project will be completed by Oncor.

20 Substation 1

Eight possible alternate sites for Substation 1 are presented in the Application. Each alternate substation location includes the same basic configuration and facilities, a 5 to 7acre site that will initially contain the following major open-air design facilities:

- Four A-frame bays
 - Four 138-kV circuit breakers
 - 10 disconnect switches
- Two 47 MVA transformers
- Two 138-kV circuit switchers
- 12 low voltage (distribution) bays at 24.9-kV

1 2	• Substation control house equipped with associated telecommunications, relay, metering, and control panels
3	• Edwards Aquafer water quality and detention pond
4	The substation will be fenced around the perimeter to ensure the safety of the public
5	and LED-lighted to adhere with industry security and safety measures and requirements.
6	The substation lighting is photocell-controlled and would typically be powered down to 20
7	percent luminosity and would power-up to 100 percent luminosity upon detection of
8	motion. A gravel access road will be built between the nearest existing road and the
9	substation.
10	PEC will own and direct the installation of the low voltage (distribution) line exits,
11	distribution line circuit breakers, and low voltage disconnect switches.
12	Substation 2
13	Eight possible alternate sites for Substation 2 are presented in the Application. Each
14	alternate substation location includes the same basic configuration and facilities, a 5 to 7-
15	acre site that will initially contain the following major open-air design facilities:
16	• Two A-frame bays
17	• Three 138-kV circuit breakers
17 18	Three 138-kV circuit breakersSeven disconnect switches
18	Seven disconnect switches
18 19	Seven disconnect switchesOne 47 MVA transformer
18 19 20	 Seven disconnect switches One 47 MVA transformer One 138-kV circuit switcher
18 19 20 21 22	 Seven disconnect switches One 47 MVA transformer One 138-kV circuit switcher Six low voltage (distribution) bays at 24.9-kV Substation control house equipped with associated telecommunications, relay,
18 19 20 21 22 23	 Seven disconnect switches One 47 MVA transformer One 138-kV circuit switcher Six low voltage (distribution) bays at 24.9-kV Substation control house equipped with associated telecommunications, relay, metering, and control panels
18 19 20 21 22 23 24	 Seven disconnect switches One 47 MVA transformer One 138-kV circuit switcher Six low voltage (distribution) bays at 24.9-kV Substation control house equipped with associated telecommunications, relay, metering, and control panels Edwards Aquafer water quality and detention pond
18 19 20 21 22 23 24 25	 Seven disconnect switches One 47 MVA transformer One 138-kV circuit switcher Six low voltage (distribution) bays at 24.9-kV Substation control house equipped with associated telecommunications, relay, metering, and control panels Edwards Aquafer water quality and detention pond The substation will be fenced around the perimeter to ensure the safety of the public
18 19 20 21 22 23 24 25 26	 Seven disconnect switches One 47 MVA transformer One 138-kV circuit switcher Six low voltage (distribution) bays at 24.9-kV Substation control house equipped with associated telecommunications, relay, metering, and control panels Edwards Aquafer water quality and detention pond The substation will be fenced around the perimeter to ensure the safety of the public and LED-lighted to adhere with industry security and safety measures and requirements.
18 19 20 21 22 23 24 25 26 27	 Seven disconnect switches One 47 MVA transformer One 138-kV circuit switcher Six low voltage (distribution) bays at 24.9-kV Substation control house equipped with associated telecommunications, relay, metering, and control panels Edwards Aquafer water quality and detention pond The substation will be fenced around the perimeter to ensure the safety of the public and LED-lighted to adhere with industry security and safety measures and requirements. The substation lighting is photocell-controlled and would typically be powered down to 20

1 PEC will own and direct the installation of the low voltage (distribution) line exits, 2 distribution line circuit breakers, and low voltage disconnect switches.

3 **Q**. 4

WHAT IS THE ESTIMATED COST OF THE NEW SUBSTATION PORTION OF **THE PROJECT?**

5 A. Attachment 4 to the Application provides the cost by substation site. These cost estimates 6 are subject to change depending on the substation site, facilities' final design, and 7 component cost variations.

8 Q. WHAT IS THE ESTIMATED COST FOR THE LCRA TSC PORTION OF THE 9 WORK AT EACH OF THE END POINTS?

10 LCRA TSC's estimated costs for the substation-related work is \$712,400 at the Leander A. 11 Substation and \$57,000 at the Round Rock Substation. These estimated costs are uniform 12 for all of the 31 routing options presented in the Application or any other route that might 13 be configured using the route segments proposed in the Application.

ARE THE PEC AND ONCOR COSTS ASSOCIATED WITH THIS PROJECT 14 Q. 15 **INCLUDED IN LCRA TCS'S COSTS ESTIMATE?**

16 No, the costs for which PEC and Oncor have responsibility are not included in LCRA A. 17 TSC's costs estimates. These costs for PEC and Oncor at the Leander and Round Rock 18 substations, respectively, are anticipated to be the same for any route approved for the 19 Project. The cost for PEC work at the Leander Substation is estimated to be approximately 20 \$600,000, and the cost for Oncor work at the Round Rock Substation is estimated to be 21 approximately \$2,000,000.

22 DO YOU FIND THE LCRA TSC COSTS TO BE REASONABLE, CUSTOMARY, 0. 23 AND SIMILAR TO OTHER PROJECTS OF SIMILAR SCOPE GIVEN THE SERVICE REQUIREMENTS OF THE PROJECT? 24

25 Yes, based on my experience with other projects of a similar scope, the substation cost A. 26 estimates presented in the Application are budgetary level estimates and are reasonable 27 based on the location of the substations and general objective of a cost estimate at this stage 28 of the Project.

1Q.ARE ALL THE IDENTIFIED POSSIBLE SUBSTATION SITES ACCEPTABLE2FOR CONSTRUCTION OF AN ELECTRICAL SUBSTATION?

A. Yes, all 16 of the new substation sites presented in the Application are acceptable for
construction of electrical substations. The sites are relatively flat, avoid the flood plain,
are of sufficient size for the intended design, and have available public access for
construction, operation, inspection, and maintenance purposes.

7 (

8

Q. PLEASE DESCRIBE THE SAFETY CONSIDERATIONS IN THE DESIGN OF THE TWO NEW SUBSTATIONS.

- 9 A. LCRA TSC will design the substations in adherence with National Electrical Safety Code
 10 (NESC) requirements. The proposed substations will be designed such that any
 11 abnormalities that could occur are contained within the perimeter of the substation.
- 12 13

VI. <u>ELECTRIC SYSTEM PLANNING PROCESS AND ERCOT</u> <u>RECOMMENDATION</u>

14 Q. DESCRIBE THE ERCOT RPG FUNCTION AND ITS REVIEW PROCESS.

15 Pursuant to Section 39.155(b) of the Public Utility Regulatory Act (PURA), ERCOT is A. 16 responsible for coordinating the transmission planning activities for transmission service 17 providers (TSPs) within its borders. To assist with this responsibility, ERCOT has 18 established a stakeholder group—the RPG—that conducts studies and reviews proposed 19 project alternatives. This group is made up of ERCOT System Planning staff, engineers 20 and/or planners from TSPs, and other stakeholders throughout ERCOT. The purpose of the 21 RPG is to consider and review proposed projects to address transmission constraints and 22 other ERCOT system needs. It is a non-voting, consensus-based organization focused on 23 identifying needs, identifying potential solutions, communicating varying viewpoints, and 24 evaluating analyses related to the ERCOT transmission grid in the planning horizon. 25 Participation in the RPG is required of all TSPs and is open to all Market Participants, 26 consumers, other stakeholders, and PUC Staff.

TSPs and other stakeholders submit project recommendations to ERCOT for review by the RPG. The RPG reviews the purpose and need for the proposed project, electrical alternatives considered, and effectiveness of the proposed solution. The RPG then

PLEASE DISCUSS HOW THE PROJECT WENT THROUGH THE RPG **Q**. **PROCESS.** A. LCRA TSC and PEC first submitted the project proposal to ERCOT for RPG review in December 2013, indicating in the proposal that the project was needed by December 31, 2018. The LCRA TSC project proposal included the new double-circuit capable 138-kV transmission line, a new load-serving substation by 2018 and another one by 2020, and the connections to the existing electrical grid. The RPG concluded that there is a need for multiple electric load-serving substations. LCRA TSC's response to comments received though the ERCOT RPG review process are provided as Exhibit SG-5. Following the RPG recommendation, the Project was reviewed by ERCOT in its independent review. The ERCOT independent review was completed on May 22, 2014. **Q**. WHAT HAS CHANGED SINCE THE TIME ERCOT REVIEWED THE **PROPOSED PROJECT?** A couple of timeframe-related matters have emerged to re-define the Project's in-service A. date and scope. First, the process to energize the new transmission line and associated first substation will be longer than the four-year lead time assumed in the planning study. Instead of completing this project by December 2018, the new in-service date is now December 2019. Second, the electric load reporting at ERCOT (Annual Load Data Request or ALDR) now includes year 2020 and the second substation is now in the ERCOT models. **O**. HAS LCRA TSC COMMUNICATED THIS CHANGE TO ERCOT? Yes. In 2015, the new load projections for the area and the revised in-service date were A. communicated to ERCOT through the various processes ERCOT has in place to communicate these types of project or system updates. First, ERCOT was notified through the filing of the ALDR in March 2015. Second, ERCOT was notified through the updates

provides comments to the requesting TSP for any clarification, if needed, to complete the

review of the project, ensuring adequate coordination and oversight.

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

of the ERCOT Power Flow cases in June 2015 where this second substation is included.
 Finally, in July 2015, LCRA TSC communicated to ERCOT the need to construct the
 second substation as part of the Project as a result of the increased electric load growth
 projections (see Attachment 3 in the Application). Specifically, LCRA TSC communicated
 that including this substation did not constitute a significant change as contemplated by
 ERCOT Nodal Protocols Section 3.11.4.10 Modifications to ERCOT Endorsed Projects.

7

8

Q. WHAT WAS ERCOT'S RESPONSE TO LCRA TSC'S NOTIFICATION OF THE NEED TO INCLUDE SUBSTATION 2 IN THE PROJECT?

- 9 A. After its review, ERCOT concurred that the inclusion of the second substation as part of
 10 the Project did not represent a significant change to the project. (See Attachment 3 to the
 11 Application.)
- 12 13

VII. <u>THE PROJECT MEETS THE CRITERIA OF PURA AND OTHER</u> <u>CRITERIA CONSIDERED BY THE COMMISSION</u>

14 Q. PLEASE SUMMARIZE YOUR FINDINGS AND RECOMMENDATIONS IN THIS 15 MATTER.

A. The Project is needed to satisfy reliability and adequacy needs for electric service in
accordance with LCRA TSC standard planning criteria and good utility practice as well as
state and federal electric service reliability standards. The Project is necessary for the
service, accommodation, convenience, and public safety, and the Project is also the best
option to meet the reliability needs when compared to other solutions including employing
distribution facilities.

Q. PLEASE SUMMARIZE THE STATE OF EXISTING SERVICE WITHOUT THE PROJECT.

A. By 2020, without the Project in service, 42 percent of the presently installed substation
transformers in the southwestern Williamson County area will exceed their rated capacity
and 90 percent will exceed their planning capacity. Furthermore, on the distribution side,
electrical loading on 27 distribution lines are projected to exceed their rated capacity and
10 distribution lines are projected to reach excessive voltage drop by 2020 without the
Project in service.

As the growth in electric demand continues and as it develops further east and away from the US Highway 183 path, PEC has exhausted opportunities to effectively, efficiently, and reliably serve the continued demand for electricity from existing load-serving substations whose capacity may be increased or new ones that may be sited adjacent to the existing transmission lines. As the electric load continues to grow, the impact to end-use consumers will increase accordingly.

7 Under the projected electric load levels, encountering certain contingencies with
8 the existing system configuration may lead to even more catastrophic failures and/or costly
9 restoration efforts.

10 Q. WILL CONSTRUCTION OF THE PROJECT RESULT IN IMPROVED SERVICE 11 OR LOWER COSTS TO THE ELECTRIC SERVICE CUSTOMERS?

12 Yes, it will result in both. The Project will provide a transmission source sized with A. 13 adequate capacity (i.e., a 138-kV, 446 MVA transmission line) to serve the long-term 14 electric service requirements at the two new substations that are required for the area. The 15 Project will result in improved electric service to end-use consumers because electric 16 system adequacy and reliability will be strengthened as described previously. The resulting 17 improved operating efficiencies (in the form of reduced electric line losses in distribution 18 and transmission facilities) will result in overall cost savings opportunities to end-use 19 consumers as well.

20Q.WHAT WILL BE THE EFFECT ON LCRA TSC AND OTHER UTILITIES IN THE21AREA IF THE PROJECT IS BUILT?

A. By implementing the Project, LCRA TSC will have met its adequacy and reliability
 obligation to electric loads connected to its system. The adequacy and reliability of the
 electric system will be enhanced for the near term and sustained for the long term for
 electric loads served in southwestern Williamson County.

5 meeting this electric load. DO THE PROPOSED ROUTING ALTERNATIVES INCLUDED IN THE 6 Q. APPLICATION (INCLUDING THE END POINTS AND THE TWO NEW 7 8 SUBSTATIONS) ADEQUATELY CONSIDER ELECTRICAL EFFICIENCY AND 9 **RELIABILITY?** 10 A. Yes, the alternative routes, new substation siting areas, and the end points associated with 11 the Project will provide for the immediate efficiency and reliability benefits envisioned and 12 supported by the directly impacted service providers. Furthermore, the transmission line 13 configuration for all of the alternative routes contained in the Application does not raise 14 any efficiency or reliability issues in addressing the identified or anticipated needs. 15 VIII. ELECTRIC SYSTEM ALTERNATIVE IMPROVEMENTS **CONSIDERED** 16 DID LCRA TSC CONSIDER DISTRIBUTION ALTERNATIVES TO THE 17 Q. 18 **PROJECT?** 19 A. Yes, the assessments conducted by PEC, and validated by LCRA TSC, considered 20 distribution solutions. However, these types of solutions were determined to be inadequate 21 for addressing the problems identified for the area. Supporting documents are provided as Attachment 6 to the Application. 22 23 PLEASE DISCUSS THE TRANSMISSION ALTERNATIVES CONSIDERED AND **Q**. 24 THE REASON FOR REJECTING ALL BUT ONE OF THEM. 25 The evaluation of transmission alternatives is described in Attachments 2 and 5 to the A. 26 Application. Alternative 11 described in Attachment 2 to the Application is the Project. 27 The Project was selected because it addresses all of the problems identified for the 28 area of concern in the most cost-effective and efficient manner. Specifically, the Project 29 provides the required 138-kV source to the project area while providing secondary benefits

IS THE PROJECT NEEDED TO CONNECT A NEW CUSTOMER OR TO

No, the Project is needed to address reliability needs of existing and future end-use

consumers based on actual and forecasted electric load and identified system limitations in

IMPROVE WHOLESALE COMPETITION?

1

2

3

4

Q.

A.

to the transmission system at the same time. The Project provides the capacity to
 accommodate a larger electric load without causing thermal violations on the transmission
 system. Lastly, the Project provides transmission service diversity, increasing reliability to
 a broader area, especially during severe weather and/or emergency conditions.

5 Q. DID LCRA TSC CONSIDER DISTRIBUTED GENERATION AS AN 6 ALTERNATIVE TO THE PROJECT?

A. Because LCRA TSC is subject to the unbundling requirements of PURA § 39.051, it is not
required to consider distributed generation as an alternative to transmission-related
problems. Furthermore, the problems identified for the area are not generation capacitybased limitations nor are the electric load levels small enough to consider distributed
generation as an economic, long-term, equal value solution.

12Q.IS THE PROJECT THE BEST ALTERNATIVE TAKING INTO ACCOUNT13CONSIDERATIONS OF EFFICIENCY, RELIABILITY, AND COST BENEFITS?

- A. Yes. After studying the needs of the area and the transmission and distribution systems
 surrounding it to serve the forecasted electric load growth, LCRA TSC determined the
 Project provides the most reliable and most efficient transmission configuration to increase
 the reliability of the transmission and distribution systems.
- 18

IX. <u>SUMMARY AND CONCLUSIONS</u>

19 Q. PLEASE SUMMARIZE YOUR CONCLUSIONS REGARDING THIS PROJECT.

A. The purpose and need for the Project has been evaluated and supported by the appropriate stakeholders (e.g., utility companies that have an obligation and are held accountable to provide reliable and cost-effective electric service; ERCOT, which is responsible for the overall reliability of the grid and for major project coordination; and public officials, who are tasked with ensuring the availability of cost-effective resources and basic utility infrastructure that supports the continued growth, health, and successful development of their communities.)

LCRA TSC has demonstrated that applicable processes and procedures, including internal, state, and national requirements, have been considered to determine the best solution, in the form of the Project, to address the issues and system limitations described in this testimony. The Project optimizes the use of existing electric system infrastructure,
 ensures the long-term adequacy of transmission service to electric loads served in the
 overall project area, and ensures the reliability of service for forecasted electric load
 growth.

5 The facilities to be added to the existing Leander and Round Rock substations and 6 installed at the two new substations are consistent with standard industry practice to 7 achieve reliable designs meeting the objective of the Project, and the associated costs are 8 reasonable.

9 The Project provides the most reliable and most efficient transmission 10 configuration to increase the reliability of the transmission and distribution systems 11 surrounding the project area when compared to other solutions such as employing 12 distribution solutions and/or other transmission solutions.

13 Q. DOES THIS CONCLUDE YOUR DIRECT TESTIMONY?

14 A. Yes, it does.